

**White  
length: 2 m**


**fully assembled DLP trunking 50 x 80**  
trunking and fittings



Selection chart (p. 706)  
 Wiring capacity chart (p. 726)

Conform to NF C 68-104

Pack	Cat.Nos	Fully assembled trunking
20 <sup>(1)</sup>	104 62	<b>Trunking without partition</b> Supplied with: – one 50 x 80 mm body – one flexible cover 65 mm wide Fits onto the whole trunking including in internal and external angles Suitable for an optimized installation with Mosaic wiring accessories by the use of Mosaic sockets with support Length 2 m
24 <sup>(1)</sup>	105 82	<b>Partition</b> Separation partition Length 2 m
20	106 91	<b>Joints</b> Body joint For aligning bases during installation
20	106 92	Body joint, attached with adhesive (fit at the end of installation)
10	108 01	Cover joint for 65 mm cover



Pack	Cat.Nos	Junctions
5	107 35	<b>Flat junction</b> For tap-off to a 80 mm wide branch
5	107 63	<b>Angled junction</b> For tap-off in an internal angle to 35 x 80, 35 x 105, 50 x 80, 50 x 105 For use with internal angles Cat.No 106 02
50	106 81	<b>Accessories</b> Clip
100	308 81	Base for clamp

**Installation accessories** (p. 724)

Pack	Cat.Nos	Angles and end cap
10	106 02	<b>Internal and external angles</b> Include the 2 components for the top and bottom of the trunking on which the flexible cover is fitted Changeable internal angle, from 85° to 95° for 50 x 80/50 x 105/50 x 150 and 50 x 195 mm trunkings
10	106 22	Changeable external angle, from 60° to 120° for 50 x 80/50 x 105/50 x 150 and 50 x 195 mm trunkings
10	107 67	<b>Flat angle</b> 90° flat angle
10	107 22	<b>End cap</b> Left or right end cap

**Other functions**

**see p. 524**

(1) Number of meters in pack